

螺纹规格	订货型号	适用电缆	螺纹外径	螺纹长度	扳手径
	黑色(B)	Cable range	O.D	Thread length	Wrench size
	灰色(G)	mm	C1 mm	C2 mm	A & F mm
M12*1.5	M12A-H2-03	3.1 ~ 2	12	9	18 / 19
	M16A-H2-04	4.1 ~ 3	16	15	22 / 22
M16*1.5	M16B-H2-04	4.1 ~ 3	16	10	22 / 22
	M16BL-H2-04	4.1 ~ 3	16	15	22 / 22
M18*1.5	M18B-H2-04	4.1 ~ 3	18	15	24/24
M20*1.5	M20A-H2-03	3.1 ~ 2	20	15	27 / 27
	M20A-H2-05	5.2 ~ 3	20	15	27 / 27
	M20A-H2-06	6.1 ~ 4.3	20	15	27 / 27
	M20B-H2-06	6.1 ~ 4.3	20	10	27 / 27
	M20BL-H2-06	6.1 ~ 4.3	20	15	27 / 27
	M20BS-H2-05	5.1 ~ 3.3	20	10	27 / 24
	M22*1.5	M22A-H2-06	6.1 ~ 4.3	22	15
M22*1.5	M22A-H2-03	3.1 ~ 2	22	15	27 / 27
	M22AS-H2-05	5.2 ~ 3	22	15	27 / 27
	M22B-H2-06	6.1 ~ 4.3	22	10	27 / 27
M25*1.5	M25A-H2-06	6.1 ~ 4.3	25	15	33 / 33
	M25A-H2-08	8.7 ~ 6.4	25	15	33 / 33
	M25A-H2-09	9.0 ~ 7.5	25	15	33 / 33
M25*1.5	M25B-H2-06	6.1 ~ 4.3	25	10	33 / 33
	M25B-H2-08	8.7 ~ 6.4	25	10	33 / 33
	M25BL-H2-08	8.7 ~ 6.4	25	15	33 / 33
	M25BS-H2-06	6.1 ~ 4.3	25	10	33 / 27
M32*1.5	M32A-H2-10	10 ~ 7.7	32	15	41 / 42
	M32A-H2-12	12 ~ 8	32	15	41 / 42

M40*1.5	M40A-H2-13	13 ~ 11	40	20	50 / 52
M50*1.5	M50A-H2-15	15 ~ 12	50	22	62/62
PG7	PG7A-H2-03	3.1 ~ 2	12.5	8.5	17 / 19
PG9	PG9A-H2-03	3.1 ~ 2	15.2	9	22 / 19
PG11	PG11A-H2-04	4.1 ~ 3	18.6	10	24 / 22
	PG11B-H2-04	4.1 ~ 3	18.6	10	24 / 22
PG13.5	PG13.5A-H2-05	5.2 ~ 3.5	20.4	10	27 / 24
	PG13.5B-H2-05	5.2 ~ 3.5	20.4	10	27 / 24
PG16	PG16A-H2-06	6.1 ~ 4.3	22.5	11	30 / 27
	PG16B-H2-06	6.1 ~ 4.3	22.5	11	30 / 27
PG21	PG21A-H2-08	8.7 ~ 6.4	28.3	12.5	36 / 33
	PG21B-H2-08	8.7 ~ 6.4	28.3	12.5	36 / 33
PG29	PG29B-H2-10	10 ~ 7.7	37	12	46 / 42
PG36	PG36B-H2-13	13 ~ 11	47	15	57 / 52
G3/8	G3/8B-H2-04	4.1 ~ 3	16.66	10	22 / 22
G1/2	G1/2B-H2-05	5.2 ~ 3.5	20.95	10	27 / 24
G3/4	G3/4B-H2-08	8.7 ~ 6.4	26.44	12.5	33 / 33
G 1"	G1B-H2-10	10 ~ 7.7	33.25	15	42 / 42
G1 1/4"	G1B 1/4-H2-13	13 ~ 11	41.91	15	53 / 52
NPT3/8	NPT3/8B-H2-04	4.1 ~ 3	17.05	13	22
NPT1/2	NPT1/2B-H2-06	6.1 ~ 4.3	21.22	13	27
NPT3/4	NPT3/4B-H2-08	8.7 ~ 6.4	26.57	15	33
NPT 1"	NPT1B-H2-10	10 ~ 7.7	33.23	17	42

型号：A型为分体结构 B型为连体结构