

螺纹规格	产品型号	适用电缆 Cable range mm	螺纹外径 O.D mm	螺纹长度 Thread length mm	扳手径 Wrench size mm
M12*1.5	M12A-H2-03-SS	3.1 ~ 2	12	9	18 / 19
M16*1.5	M16A-H2-04-SS	4.1 ~ 3	16	15	22 / 22
M20*1.5	M20A-H2-03-SS	3.1 ~ 2	20	15	27 / 27
	M20A-H2-05-SS	5.2 ~ 3	20	15	27 / 27
	M20A-H2-06-SS	6.1 ~ 4.3	20	15	27 / 27
M22*1.5	M22A-H2-06-SS	6.1 ~ 4.3	22	15	27 / 27
	M22A-H2-03-SS	3.1 ~ 2	22	15	27 / 27
	M22AS-H2-05-SS	5.2 ~ 3	22	15	27 / 27
M25*1.5	M25A-H2-06-SS	6.1 ~ 4.3	25	15	33 / 33
	M25A-H2-08-SS	8.7 ~ 6.4	25	15	33 / 33
	M25A-H2-09-SS	9.0 ~ 7.5	25	15	33 / 33
M32*1.5	M32A-H2-10-SS	10 ~ 7.7	32	15	41 / 42
M40*1.5	M40A-H2-13-SS	13 ~ 11	40	20	50 / 52
M50*1.5	M50A-H2-15-SS	15 ~ 12	50	22	62/62
PG7	PG7A-H2-03-SS	3.1 ~ 2	12.5	8.5	17 / 19
PG9	PG9A-H2-03-SS	3.1 ~ 2	15.2	9	22 / 19
PG11	PG11A-H2-04-SS	4.1 ~ 3	18.6	10	24 / 22
PG13.5	PG13.5A-H2-05-SS	5.2 ~ 3.5	20.4	10	27 / 24
PG16	PG16A-H2-06-SS	6.1 ~ 4.3	22.5	11	30 / 27
PG21	PG21A-H2-08-SS	8.7 ~ 6.4	28.3	12.5	36 / 33

该产品可定制各类材质、内外螺纹等；如有需求请咨询销售部。