

| 型号     | 公制规格  | 英制规格   | 外径及允许偏差 (mm) | 自然弯曲 (mm) | 轴向拉力 (Kg) | 包装单位 (m) |
|--------|-------|--------|--------------|-----------|-----------|----------|
| PM-6   | Φ 6   | 3/16"  | 9.00 ± 0.25  | 40        | 335       | 200      |
| PM-8   | Φ 8   | 1/4"   | 11.8 ± 0.30  | 45        | 470       | 100      |
| PM-10  | Φ 10  | 5/16"  | 14.5 ± 0.30  | 55        | 590       | 100      |
| PM-12  | Φ 12  | -      | 16.5 ± 0.35  | 60        | 710       | 100      |
| PM-13  | Φ 13  | 3/8"   | 17.5 ± 0.35  | 65        | 765       | 100      |
| PM-15  | Φ 15  | -      | 20.2 ± 0.35  | 80        | 885       | 100      |
| PM-16  | Φ 16  | 1/2"   | 21.2 ± 0.35  | 85        | 940       | 100      |
| PM-19  | Φ 19  | -      | 24.5 ± 0.40  | 95        | 1120      | 50       |
| PM-20  | Φ 20  | 3/4"   | 25.5 ± 0.40  | 100       | 1180      | 50       |
| PM-25  | Φ 25  | 1"     | 31.7 ± 0.45  | 120       | 1450      | 50       |
| PM-32  | Φ 32  | 1 1/4" | 39.6 ± 0.50  | 150       | 1885      | 25       |
| PM-38  | Φ 38  | 1 1/2" | 46.6 ± 0.60  | 180       | 2240      | 25       |
| PM-51  | Φ 51  | 2"     | 59.5 ± 1.00  | 220       | 3000      | 20       |
| PM-64  | Φ 64  | 2 1/2" | 73.5 ± 1.50  | 310       | 3770      | 10       |
| PM-75  | Φ 75  | 3"     | 84.5 ± 2.00  | 350       | 4400      | 10       |
| PM-100 | Φ 100 | 4"     | 109.0 ± 3.0  | 410       | 4700      | 10       |

新品持续更新中，如有需求请联系销售部。