

螺牙规格	适用电缆外径范围	mm	螺纹外径	螺纹长度	扳手径	螺距
			C1mm	C2 mm	A & F mm	
M8	M8B-06	2-4.7	8	6	13/14	1
	M8B-06	2-4.9	8	6	14/14	1.25
M10	M10B-06	3.0-6.8	10	6	14/14	1.25
	M10B-06	2.5-6.5	10	6	14/14	1.5
M12	M12B-06	3-6.4	12	6	14/14	1.5
	M12B-08	3.5-8	12	6	17/18	1.5
M14	M14B-06	2.5-6.4	14	6	16/14	1.5
M16	M16B-08	3.5-8	16	7	18/18	1.5
	M16B-10	5.0-10	16	7	18/20	1.5
M18	M18B-10	4.5-10	18	7.8	20/20	1.5
M20	M20B-08	3.0-8	20	8	23/18	1.5
	M20B-10	5.0-10	20	8	23/20	1.5
	M20B-12	6.5-12	20	8	23/22	1.5
	M20B-14	9--13.8	20	8	23/24	1.5
M22	M22B-14	9.8-14	22	9	24-24	1.5
M24	M24B-14	9.8-14	24	9.5	27/24	1.5
M25	M25B-14	10.0-14	25	10	28/24	1.5
	M25B-16	11.8-16	25	10	28/28	1.5
M27	M27B-18	10.0-18	27	10.8	30/30	2
M30	M30B-12	8.0-12	30	11	32/32	2
	M30B-18	13.0-18	30	11	32/32	2
	M30B-20	14-20	30	11	32/32	2
M32	M32B-22	17-22	32	11	36/35	1.5

M33	M33B-22	15-22	33	11	36/36	2
M36	M36B-25	18-25	36	12	40-40	2
M40	M40B-28	22-28	40	12.5	42-42	1.5
M42	M42B-28	22-27.8	42	12.5	45-42	2
M48	M48B-32	25-32	47.7	13	52-52	2
M50	M50B-38	28-36	49.7	13	54-54	1.5
M63	M63B-44	34-44	62.6	14	70-64	1.5
M64	M64B-44	32-44	63.6	14.5	70-64	2
M72	M72B-52	42-52.5	71.5	15.5	78-78	2
M76	M76B-55	47-55.5	75.6	15.5	82-82	2
M80	M80B-60	51-60.5	79.5	16.5	88-88	2
M88	M88B-72	56-72	87.5	21	98-98	2
M100	M100B-82	82-77	99.5	23	110-110	2
M110	M110B-98	98-88	109.5	25	120-120	2
M125	M125B-108	108-98	124.5	25	135-135	2

该产品可定制各类材质、内外螺纹等；如有需求请咨询销售部。