

螺牙规格	订货型号	电缆外径密封范围		螺纹长度	钢带厚度		网带厚度	最大直径B
		A (mm)	B (mm)	L (mm)	min	max	(mm)Max	(mm)Max
M20	EXd-M20-14	3.1~5	5.0~14.0	15	0.1	0.4	0.85	24
	EXd-M20-16	7~13	6.5~16	15	0.1	0.4	0.9	27
M25	EXd-M25-20	12~16	9.5~20	15	0.1	0.4	0.9	30
	EXd-M25-25	13~17	10~25	15	0.1	0.7	1.4	38
M32	EXd-M32-25	16~20	10~25	15	0.1	0.7	1.4	38
	EXd-M32-30	18~23	12~30	15	0.1	0.7	1.4	46
M40	EXd-M40-30	24~29	12~30	16	0.1	0.7	1.6/2.0	46
	EXd-M40-38	25~30	14~38	16	0.1	0.8	1.4	55
M50	EXd-M50-38	30~35	14~38	17	0.2	0.8	2.5	55
	EXd-M50-48	40~45	20~48	17	0.2	0.63	1.4	68
M63	EXd-M63-48	40~45	20~48	17	0.2	0.63	2.0/2.5	68
	EXd-M63-58	40.1~51	24~58	17	0.2	0.63	1.5	84
M75	EXd-M75-58	46~50	24~58	19	0.3	0.63	2.5	84
	EXd-M75-70	46~50	30~70	19	0.3	0.81	1.5	100
M88	EXd-M88-70	60~65	30~70	19	0.3	0.81	2.5	100
M100	EXd-M100-100	78~85	45~102	19	0.3	0.81	2.5/3.15	125
M110	EXd-M110-100	80~90	45~102	19	0.3	0.94	1.6	125
M125	EXd-M125-100	80~95	45~102	19	0.3	0.936	1.6	140

螺牙规格	订货号	电缆外径密封范围		螺纹长度	钢带最大厚度		网带厚度	最大直径B
		A (mm)	B (mm)	L (mm)	min	max	(mm)Max	(mm)Max
NPT1/2	EXd-NPT1/2-14	3.1~5	5.0~14.0	15	0.1	0.4	0.85	24
	EXd-NPT1/2-16	7~13	6.5~16	15	0.1	0.4	0.9	27
NPT3/4	EXd-NPT3/4-20	12~16	9.5~20	15	0.1	0.4	0.9	30
	EXd-NPT3/4-25	13~17	10~25	15	0.1	0.7	1.4	38
NPT 1"	EXd-NPT1-25	16~20	10~25	15	0.1	0.7	1.4	38

NPT 1"	EXd-NPT1-30	18~23	12~30	15	0.1	0.7	1.4	46
NPT1 1/4"	EXd-NPT1-1/4-30	24~29	12~30	16	0.1	0.7	1.6/2.0	46
	EXd-NPT1-1/4-38	25~30	14~38	16	0.1	0.8	1.4	55
NPT1 1/2"	EXd-NPT1-1/2-38	30~35	14~38	17	0.2	0.8	2.5	55
	EXd-NPT1-1/2-48	40~45	20~48	17	0.2	0.63	1.4	68
NPT 2"	EXd-NPT2-48	40~45	20~48	17	0.2	0.63	2.0/2.5	84
	EXd-NPT2-58	40.1~51	24~58	17	0.2	0.63	1.5	84
NPT2 1/2"	EXd-NPT2 1/2-58	46~50	24~58	19	0.3	0.63	2.5	84
	EXd-NPT2 1/2-70	46~50	30~70	19	0.3	0.81	1.5	100
NPT 3"	EXd-NPT3-70	60~65	30~70	19	0.3	0.81	2.5	100
NPT 4"	EXd-NPT4-100	78~85	45~102	19	0.3	0.936	1.6	125

螺牙规格		电缆外径密封范围		螺纹长度	钢带最大厚度		网带厚度	最大直径B
英制		A(mm)	B(mm)	L(mm)	min	max	(mm)Max	(mm)Max
G1/2"	EXd-G1/2-14	3.1~5	5.0~14.0	15	0.1	0.4	0.85	24
	EXd-G1/2-16	7~13	6.5~16	15	0.1	0.4	0.9	27
G3/4"	EXd-G3/4-20	12~16	9.5~20	15	0.1	0.4	0.9	30
	EXd-G3/4-25	13~17	10~25	15	0.1	0.7	1.4	38
G 1"	EXd-G1-25	16~20	10~25	15	0.1	0.7	1.4	38
	EXd-G1-30	18~23	12~30	15	0.1	0.7	1.4	46
G1 1/4"	EXd-G1-1/4-30	24~29	12~30	16	0.1	0.7	1.6/2.0	46
	EXd-G1-1/4-38	25~30	14~38	16	0.1	0.8	1.4	55
G1 1/2"	EXd-G1-1/2-38	30~35	14~38	17	0.2	0.8	2.5	55
	EXd-G1-1/2-48	40~45	20~48	17	0.2	0.63	1.4	68
G 2"	EXd-G2-48	40~45	20~48	17	0.2	0.63	2.0/2.5	84
	EXd-G2-58	40.1~51	24~58	17	0.2	0.63	1.5	84
G2 1/2"	EXd-G2-1/2-58	46~50	24~58	19	0.3	0.63	2.5	84
	EXd-G2-1/2-70	46~50	30~70	19	0.3	0.81	1.5	100
G 3"	EXd-G3-70	60~65	30~70	19	0.3	0.81	2.5	100
G 4"	EXd-G4-100	78~85	45~102	19	0.3	0.936	1.6	125

