

螺纹规格	产品型号	适用电缆 Cable range mm	螺纹外径 O.D mm	螺纹长度 Thread length mm	扳手径 Wrench size mm
M12*1.5	M12A-H3-02-SS	2.6 ~ 1.0	12	9	18 / 19
M16*1.5	M16A-H3-03-SS	3 ~ 1	16	15	22 / 22
	M16A-H3-04-SS	4.2 ~ 3	16	15	22 / 22
M20*1.5	M20A-H3-03-SS	3.1 ~ 2	20	15	27 / 27
	M20A-H3-05-SS	5.2 ~ 3.5	20	15	27 / 27
M22*1.5	M22A-H3-05-SS	5.2 ~ 3	22	15	30 / 30
M25*1.5	M25A-H3-05-SS	5.2 ~ 3	25	15	33 / 33
	M25A-H3-07-SS	6.1 ~ 3.3	25	15	33 / 33
	M25A-H3-08-SS	8 ~ 6.2	25	15	33 / 33
	M25A-H3-08-ST-SS	8 ~ 6.2	25	10	33 / 33
M32*1.5	M32A-H3-10-SS	10 ~ 7.7	32	15	41 / 42
M40*1.5	M40A-H3-10-SS	10 ~ 7.7	40	20	50 / 52
	M40A-H3-12-SS	12 ~ 9	40	20	50 / 52
	M40A-H3-13-SS	13 ~ 10	40	20	50 / 52
M50*1.5	M50A-H3-12-SS	12 ~ 9	50	22	62/62
	M50A-H10-08-SS	8 ~ 6	50	22	62/62
M63*1.5	M63A-H3-13-SS	13 ~ 10	63	25	75/78
PG7	PG7A-H3-02-SS	2.6 ~ 1.6	12.5	8.5	17 / 19
PG9	PG9A-H3-02-SS	2.6 ~ 1.6	15.2	9	22 / 19
PG11	PG11A-H3-04-SS	4.2 ~ 3	18.6	10	24 / 22
PG13.5	PG13.5A-H3-05-SS	5 ~ 3.5	20.4	10	27 / 24
PG16	PG16A-H3-05-SS	5.2 ~ 3.5	22.5	11	30 / 27
	PG16A-H3-06-SS	6.2 ~ 4	22.5	11	30 / 27

PG21	PG21A-H3-05-SS	5 ~ 3.5	28.3	12.5	36 / 33
	PG21A-H3-08-SS	8 ~ 6.2	28.3	12.5	36 / 33
PG29	PG29A-H3-10-SS	10 ~ 7.7	37	12	46 / 42
PG36	PG36A-H3-10-SS	10 ~ 7.7	47	15	57 / 52

该产品可定制各类材质、内外螺纹等；如有需求请咨询销售部。